

RIG 2

TECHNICAL OVERVIEW

Rating	300 HP	223 kW
Hook load	205,000 lbs @ 8 lines	93 t
Drilling depth	4,000 ft w/4,5" DP	1,219 m

MAST

Make	L.C. MOORE	
Type	Cantilever	
Height	96 ft	29.2 m
Hook load	205,000 lbs	93 T
GNC	290,000 lbs	131 T

SUBSTRUCTURE

Make	L.C MOORE	
Type	Pin Type	
Height	7 ft	2.13 m
Casing load	N/A	
Setback load	N/A	

DRAWWORKS

Type	NATIONALI T-20	
Horsepower rating	300 HP	223 kW
Max. line pull	27,800 lbs	12.6 T
Drilling line diameter	1"	25 mm
Auxiliary brake	Parmac 15" D.R.	

TOP DRIVE

Type	N/A
Capacity	N/A
Continuous Torque	N/A

ROTARY TABLE (ASSISTING)

Type	JUMBO BUSTER	
Table opening	17 1/2"	444.5 mm

DRIVE GROUP

Engine type	2 x GM 6 X 71
Horsepower rating	2 x 250 HP



MUD SYSTEM

Pump type	1 x NATIONAL IDEAL C-250 + 1 x NATIONAL IDEAL C-150	
Horsepower rating	1 x 250 HP + 1 x 150 HP	
Shale shaker(s)	2 pc, VSM-300	
Mud system capacity	1,420 bbl	225 m³

BOP EQUIPMENT

Annular	13 5/8" x 5,000 psi
Single ram	13 5/8" x 5,000 psi
Double ram	13 5/8" x 5,000 psi

CAMP EQUIPMENT

- Full rig and base camp

ADDITIONAL INFORMATION

- 21 1/4" x 2,000 psi annular can be provided upon customer request